

## ICB-N2034

4MP, Human Detection Smart, Dual Light Bullet Camera

### Highlights

- Max. image resolution: **4MP(2560x1440)**
- H.265 high effective compression
- IR distance can reach 15M
- IP66 Plastic casing
- Support bidirectional talk



4MP

H.265

IP66

### Specifications

<b>Model</b>	ICB-N2034
<b>Basic Parameter</b>	
<b>Smart Function</b>	Human detection
<b>Image Sensor</b>	1/2.7", 4MP progressive scan ultra-low illumination CMOS GC4653
<b>Effective Pixels</b>	4MP
<b>Min. Illumination</b>	Color: 0.1Lux@F1.2; B&W: 0Lux@F1.2(IR on)
<b>Lens</b>	F1.6 4mm
<b>IR Distance</b>	15M (4pcs dual light)
<b>Noise Reduction</b>	3D digital noise reduction
<b>WDR</b>	DWDR (Off/Low/Medium/High)
<b>Mirror</b>	Off/Horizontal mirroring/Vertical mirroring/180° rotation
<b>Image Setting</b>	Brightness/Contrast/Sharpness/Saturation/Chroma
<b>Human Detection</b>	
<b>Responding Speed</b>	≤1s
<b>Max. Detection Frame Rate</b>	5fps/s (color image)
<b>Detection Area</b>	Support specified area, default full screen
<b>Shielded Area</b>	Support 4 areas setting
<b>Upload Method</b>	Private protocol upload
<b>Trigger Method</b>	Video trigger
<b>Video and Audio Coding</b>	
<b>Encoding Format</b>	S265/H.265/H.264
<b>Coding Characteristics</b>	Main stream: 2592x1904@20fps, 2560x1440@25fps, 2304x1296@25fps, 1920x1080@25fps Sub-stream: D1(720x576), VGA(640x480), Q720P(640x360)
<b>Video Bit Rate</b>	Fixed bit rate, variable bit rate(1280kbps-4Mbps)
<b>Video Type</b>	Composite stream/Video stream
<b>Audio Coding Standard</b>	G.711U/64Kbps

## ICB-N2034

4MP, Human Detection Smart, Dual Light Bullet Camera

## Specifications

Network	
<b>Ethernet Interface</b>	1x RJ45 10M/100M self-adaptive Ethernet port
<b>Network Protocol</b>	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTSP, RTMP, DDNS, UPnP, NTP, SMTP
<b>Interface Protocol</b>	Onvif/SLINK
<b>Preview Monitoring</b>	Mobile Phone/IMS/NVR/Browser
<b>Simultaneous Live View</b>	Up to 2-ch
<b>User</b>	User add/Modify/Delete, permission management
<b>Security</b>	Authorized user name and password, HTTPS encryption and AES link encryption, RTSP
General	
<b>Power Supply</b>	PoE (802.3at) / DC 12V
<b>Power Consumption</b>	≤10W
<b>Dimensions(mm)</b>	58.47mm x 58.47mm x 183.74mm
<b>Operating Temperature</b>	-20°C ~ 55°C
<b>Operating Humidity</b>	0%-90%
<b>Protection Grade</b>	IP66
<b>Weight</b>	350g